



INDUSTRIAL CYLINDER HEATED DRYING IRONERS

FCI500

FEATURES

- Large surface contact with linen over an angle of 300°
- Finger protection and emergency button for more safety
- Durable Meta Aramid ironing belts
- Automatic cooldown
- Easy-to-operate microprocessor: 20 pre-set ironing programs
- Indication of ironing speed and temperature
- Reverse mode possible
- Frequency controlled motor
- Easy-to-remove lint filters
- Space saving installation against the wall is possible: front return
- Electric, gas or steam heating

OPTIONS

- Coin operated version
- Foot pedal for easy start and stop operation
- Chrome-plated cylinder for a better thermal conduction



ROBUST
DESIGN



HIGH OUTPUT



LOW ENERGY
CONSUMPTION

THE SMART LAUNDRY PARTNER

	FCI 1600 / 500	FCI 2000 / 500	FCI 2600 / 500	FCI 3200 / 500
ROLLER DIAMETER (MM)	502	502	502	502
USEFUL ROLLER LENGTH (MM)	1600	2000	2600	3200
IRONING CAPACITY*				
ELECTRICAL AND GAS HEATING (KG/H)	65	80	95	120
STEAM HEATING (KG/H)	80	95	115	145
HEATING				
ELECTRIC (KW)	32,4	37,2	54	64,8
GAS (KW)	30	36	52	66
STEAM (KG/H)	36	49	68	88
MOTOR				
ROLLER MOTOR (KW)	0,37	0,37	0,37	0,37
FAN MOTOR (KW)	0,18 (50Hz) / 0,255 (60Hz)	0,18 (50Hz) / 0,255 (60Hz)	2 x 0,18(50Hz) / x 0,255 (60Hz)	2 x 0,18(50Hz) / x 0,255 (60Hz)
EXHAUST VENTILATION (MM)	1 x 150	1 x 150	2 x 150	2 x 150
ROLLER SPEED (M/MIN)	1,5 - 8	1,5 - 8	1,5 - 8	1,5 - 8
ELECTRICAL CONNECTIONS				
	3 x 380-415V+N 5/60Hz 3 x 208-240V 50/60Hz 3 x 380-415/440V 50/60Hz	3 x 380-415V+N 5/60Hz 3 x 208-240V 50/60Hz 3 x 380-415/440V 50/60Hz	3 x 380-415V+N 5/60Hz 3 x 208-240V 50/60Hz 3 x 380-415/440V 50/60Hz	3 x 380-415V+N 5/60Hz 3 x 208-240V 50/60Hz 3 x 380-415/440V 50/60Hz
TRANSPORT DATA				
NET WEIGHT (KG)	890 (E) / 900 (S) / 920 (G)	1020 (E) / 1070 (S) / 1150 (G)	1260 (E) / 1280 (S) / 1290 (G)	1470 (E) / 1540 (S) / 1590 (G)
GROSS WEIGHT (KG)	1130 (E) / 1140 (S) / 920 (G)	1285 (E) / 1335 (S) / 1415 (G)	1580 (E) / 1600 (S) / 1610 (G)	1830 (E) / 1900 (S) / 1950 (G)
DIMENSIONS H X W X D (MM)	1232 x 2350 x 1052	1232 x 2750 x 1052	1232 x 3350 x 1087	1232 x 3950 x 1087
PACKING DIMENSIONS H X W X D (MM)	1550 x 2485 x 1095	1550 x 2885 x 1095	1550 x 3485 x 1095	1550 x 4085 x 1095

* Data from lab according to standard ISO9398-1. The actual capacity depends on laundry conditions and operators which could be 20% -40% lower.

