

BR 25_50_65_90

+ BR 25



+ 50 - 65 - 90
+ SERBATOIO/TANK



+ BR 50 - 65 - 90
SENZA SERBATOIO/WITHOUT TANK



+ BR 50 - 65 - 90
1+1



BR 25_50_65_90



BR 25 Electric steam generators, with electronic water level controls, designed and built for an easy and quick installation. All components are easily accessible allowing simple, straightforward routine maintenance. These steam generators are built with high grade materials and conform to PED European Standards.

The BR 25 65 and 90 models are also available in a 7-bar working-pressure version, which is perfect to obtain optimal performance from a Shirt finisher, a Collar & Cuff Press and for our LAV PRESS Series with polished head.

The ENERGY SAVER device is built with an upgraded pump and solenoid valve, and with a special tank to supply hot water back to the boiler up to 90°C, allowing significant energy savings.

THE KIT 1+1 ALLOWS TWO SIMILAR STEAM GENERATORS TO BE MOUNTED ON TOP OF EACH OTHER, COMPLETE WITH FEEDING TANK, THERE BY DOUBLING ITS POWER AND ALSO ITS HOURLY STEAM PRODUCTION.

For models, powers and versions, see the corresponding chart.



Available extras upon request:

- feeding tank for water supply and condensate return completely built in stainless steel;
- casters with support

TECHNICAL DATA		BR 25	BR 50	BR 65	BR 90
POWER		400/3+N/50 • 230V/3/60 Hz*			
PUMP MOTOR		0,5 kW			
WATER FEEDING		Rubber tube Ø 13 mm • Ø 0,5 in			
STEAM DRAWING		1/2"			
BOILER DRAIN		1/2"			
BOILER CAPACITY		20 lt	30 lt	55 lt	
DIMENSIONS	670 x 510 x 855 mm	680 x 880 x 990 mm • 25,5 x 34,5 x 395 in			
	26,5 x 20 x 33,6 in				
ENCUMB. WITH TANK	670 x 525 x 1215 mm	650 x 880 x 1310 mm • 25,5 x 34,5 x 51,5 in			
	26,5 x 20,5 x 48 in				
ENCUMB. 1+1		715 x 865 x 2135 mm • 28 x 34 x 84 in			
GROSS WEIGHT		103 kg • 227 Lbs	171 kg • 377 Lbs	176 kg • 388 Lbs	
GROSS WEIGHT WITH TANK		140 kg • 308,6 Lbs	218 kg • 480,6 Lbs	225 kg • 496 Lbs	
GROSS WEIGHT 1+1		-	375 kg • 826,7 Lbs	400 kg • 881,8 Lbs	
PACKAGE DIMENSIONS		800 x 840 x 1570 mm • 31,5 x 33 x 61,8 in			
PACKAGE DIMENSIONS WITH TANK		800 x 840 x 1570 mm • 31,5 x 33 x 61,8 in			
PACKAGE DIMENSIONS 1+1		-	800 x 840 x 2250 mm • 31,5 x 33 x 88,6 in		
POWER IN KW • DHP		10-1 • 12-1,2 • 15-1,5 • 18-1,8	24-2,4 • 26-2,6 • 28-2,8 30-3 • 33-3,3 • 36-3,6	30-3 • 36-3,6 • 42-4,2 • 48-4,8	54-5,4 • 60-6 • 66-6,6
STEAM PRODUCTION KG/H • LBS/H		13-28 • 16-35 • 20-44 • 25-55	33-72 • 36-79 • 38-83 41-90 • 45-99 • 49-108	41-90 • 49-108 57-125 • 65-143	74-163 • 82-180 • 90-198
STEAM WORKING PRESSURE		6 bar • 87 psi	5 bar • 72,5 psi	6 bar • 87 psi	6 bar • 87 psi
KIT 1+1			•	•	•
*Other voltages by request.					

*Other voltages by request.

For manufacturing necessities the above-mentioned specifications are not binding.